

Spa Start Up Check List

Fill hot tub by placing hose into the filter cavity and opening the bleeder valves. The filters may remain in place as well as the floating basket. Do not fill the hot tub until the electrical work has been completed. Fill the tub to the middle of the tile line. If your tub does not have tiles, fill it to the middle of the V. _____/ When the tub has reached its proper fill level, the power may be switched on.

The tub will begin to heat. @home model hot tubs will heat by running the jets, and the Reflections line will heat by using the circulation pump, not the jets. Both the jets or circ pump will run until the hot tub has reached the temperature selected on the control panel. The temperature reading on the control panel will read the temperature of the water. To select the temperature that you wish the spa to reach, press the + symbol to raise the temperature or the - symbol to decrease the temperature. This will be your "Set point".

At this point you may begin treating your water. All water out of the tap will be sanitized, it will also have an amount of minerals and metals dissolved in the water, and will have a low PH level. These minerals and metals will be filtered out of the water within the first week or so and the filters will be required to be cleaned twice the first week and thereafter only once a month.

When cleaning your filters monthly also check the water with your test strips for proper PH and or other chemical levels depending upon what sanitation regimen you are using. Add two tablespoons of SHOCK, or add according to the manufacturer's directions, Chlorine or bromine.

Proper water treatment will only work when the spa is being properly filtered. When using a Vision cartridge, if you have two filters, place it on the top of the filter underneath the one piece cover; and if you have one filter, place it under the floating strainer basket on the filter. When removing the filters to clean, shut off the power to the spa or place the spa into standby mode, and always remember this is a non-force procedure. Turn the filter to the left ½ turn then pull up on one of the 4 tabs and remove the filter. After having the filter removed from the filter cavity, clean the filter with your garden hose using the jet setting on your hose. The better you clean your filters the longer they will last. Try to spread each vein of the filter paper and clean using the jet setting from top to bottom.

Water Chemistry Guidelines

When adding any chemicals to your spa, run all the jets on high. While leaving the jets on, add the chemicals. Leave the jets running until they automatically shut off. This will ensure proper mixture of the chemicals into the water.

When using Shock, Shock hot tub with D1 shock treatment as follows:

If using hot tub 1 – 3 times a week, shock once a week, 2 oz. per dosage

If using hot tub 4 – 6 times a week, shock twice a week, 2 oz., per dosage

When using Chlorine or bromine, follow the manufacture's directions.

Maintain PH between 7.2 –7.8. This will allow the chemical regimen to work properly as well as keep the plastics soft.